



SOUTHERN CONCRETE SDN. BHD. (385615-W)

Address: PT 1097, 2 1/2KM, Off Jalan Pengkalan, Mukim Sg. Raya, 31300 Kg. Kepayang,
Perak Darul Ridzuan, Malaysia.

Tel: 605-357 4950

Fax: 605-357 4945

One Meter Length

Southern Concrete Reinforced Concrete Spun Pipe are manufactured in compliance to M.S 881 PT.3:1991 & B.S 5911 PT.3:1982

their range are available from 300mm $\varnothing$ to 1500mm $\varnothing$ with Rebated/Ogee joint.

There are two classes: -

S - Standard Reinforced

X/L Extra Strength Reinforced

Y/M Special Strength Reinforced

Z/H Special Strength Reinforced



Nominal $\varnothing$ mm (in)	Nominal Length L mm	Internal $\varnothing$ I $\varnothing$ mm	External $\varnothing$ E $\varnothing$ mm	Wall Thickness mm	Approx Weight Per Pipe			
					S Tonne	X / L Tonne	Y / M Tonne	Z / H Tonne
300 12	1500	300	364	32	0.122	0.122	0.130	0.132
375 15	1500	375	445	35	0.146	0.146	0.155	0.157
450 18	1500	450	536	43	0.196	0.196	0.206	0.208
600 24	1500	600	700	50	0.334	0.334	0.346	0.346
750 30	1500	750	862	56	0.443	0.453	0.455	0.463
900 36	1500	900	1020	60	0.556	0.566	0.573	0.580
1050 42	1500	1050	1178	64	0.778	0.792	0.802	0.812
1200 48	1500	1200	1336	68	1.030	1.050	1.057	1.082
1500 60	1500	1500	1650	75	1.390	1.442	1.442	1.506